

# Pro Stock Tractor Rules

1. Maximum weight permitted is 10,000lb.
2. Maximum cubic inch limit is 680. Maximum of 8 cylinders permitted. Acceptable blocks must have come from 2WD tractors. OEM aftermarket replacement blocks permitted, which will follow these guidelines:
  - . 6 cylinder maximum
  - . Acceptable blocks must have come from 2WD tractors.
  - . Camshaft must remain in the OEM location. No overhead cams permitted.
  - . Fuel injection pump must remain in OEM location.
  - . Height maximum - center of crankshaft to cylinder head surface not to exceed one inch over OEM dimension (block, gaskets, deck/spacer plates.)
  - . Engine block must have marking/casting indication from manufacturer.
  - . Block may be inspected by official before assembly and being placed into service.
3. The only acceptable fuel is diesel fuel.
4. No combustible agents allowed in water injection.
5. One turbo-charge is allowed, as is one pressure stage and one air compressing device. Turbo-charger's compressor housing must be wrapped with a Kevlar style blanket. Exhaust elbows are recommended to be schedule 10 pipe.
6. Intercoolers are permitted.
7. Maximum tire size should not exceed 24.5 x 32.
8. All Pro-Stock tractors will require a 47.1 SFI Spec rollover protection.
9. All other tractor rules apply.